


Produits > Instrumentation > Clapets

700 séries



Référence	Matériel	Cv	H	H1	L	I	Inlet End Connection	Orifice	Outlet End Connection
CV1-H-2T-S316	316 Stainless Steel	0.16	11.11 mm	15.88 mm	55.60 mm	25.00 mm	1/8" Hy-Lok	4.8 mm	1/8" Hy-Lok
CV1-H-2T-BRAS	Brass	0.16	11.11 mm	15.88 mm	55.60 mm	25.00 mm	1/8" Hy-Lok	4.8 mm	1/8" Hy-Lok
CV1-M-2N-S316	316 Stainless Steel	0.47	N/A	15.88 mm	44.40 mm	25.00 mm	1/8" Male NPT	4.8 mm	1/8" Male NPT
CV1-M-2N-BRAS	Brass	0.47	N/A	15.88 mm	44.40 mm	25.00 mm	1/8" Male NPT	4.8 mm	1/8" Male NPT
CV1-F-2N-S316	316 Stainless Steel	0.47	N/A	15.88 mm	46.60 mm	N/A	1/8" Female NPT	4.8 mm	1/8" Female NPT
CV1-F-2N-BRAS	Brass	0.47	N/A	15.88 mm	46.60 mm	N/A	1/8" Female NPT	4.8 mm	1/8" Female NPT
CV1-H-4T-S316	316 Stainless Steel	0.47	14.29 mm	15.88 mm	60.00 mm	25.00 mm	1/4" Hy-Lok	4.8 mm	1/4" Hy-Lok
CV1-H-4T-BRAS	Brass	0.47	14.29 mm	15.88 mm	60.00 mm	25.00 mm	1/4" Hy-Lok	4.8 mm	1/4" Hy-Lok
CV1-H-6M-S316	316 Stainless Steel	0.47	14.00 mm	15.88 mm	60.00 mm	25.00 mm	6mm Hy-Lok	4.8 mm	6mm Hy-Lok
CV1-H-6M-BRAS	Brass	0.47	14.00 mm	15.88 mm	60.00 mm	25.00 mm	6mm Hy-Lok	4.8 mm	6mm Hy-Lok

Référence	Matériel	Cv	H	H1	L	I	Inlet End Connection	Orifice	Outlet End Connection
CV1-MH-4N4T-S316	316 Stainless Steel	0.47	14.29 mm	15.88 mm	56.40 mm	25.00 mm	1/4" Male NPT	4.8 mm	1/4" Male NPT
CV1-MH-4N4T-BRAS	Brass	0.47	14.29 mm	15.88 mm	56.40 mm	25.00 mm	1/4" Male NPT	4.8 mm	1/4" Male NPT
CV1-M-4N-S316	316 Stainless Steel	0.47	N/A	15.88 mm	53.40 mm	25.00 mm	1/4" Male NPT	4.8 mm	1/4" Male NPT
CV1-M-4N-BRAS	Brass	0.47	N/A	15.88 mm	53.40 mm	25.00 mm	1/4" Male NPT	4.8 mm	1/4" Male NPT
CV1-F-4N-S316	316 Stainless Steel	0.47	N/A	19.05 mm	54.60 mm	25.00 mm	1/4" Female NPT	4.8 mm	1/4" Female NPT
CV1-F-4N-BRAS	Brass	0.47	N/A	19.05 mm	54.60 mm	25.00 mm	1/4" Female NPT	4.8 mm	1/4" Female NPT
CV2-H-6T-S316	316 Stainless Steel	1.48	17.46 mm	22.22 mm	74.80 mm	36.20 mm	3/8" Hy-Lok	7.1 mm	3/8" Hy-Lok
CV2-H-6T-BRAS	Brass	1.48	17.46 mm	22.22 mm	74.80 mm	36.20 mm	3/8" Hy-Lok	7.1 mm	3/8" Hy-Lok
CV2-H-10M-S316	316 Stainless Steel	1.48	19.00 mm	22.22 mm	74.80 mm	36.20 mm	10mm Hy-Lok	7.1 mm	10mm Hy-Lok
CV2-H-10M-BRAS	Brass	1.48	19.00 mm	22.22 mm	74.80 mm	36.20 mm	10mm Hy-Lok	7.1 mm	10mm Hy-Lok
CV2-M-6N-S316	316 Stainless Steel	1.48	N/A	22.22 mm	64.60 mm	36.20 mm	3/8" Male NPT	7.1 mm	3/8" Male NPT
CV2-M-6N-BRAS	Brass	1.48	N/A	22.22 mm	64.60 mm	36.20 mm	3/8" Male NPT	7.1 mm	3/8" Male NPT
CV3-F-6N-S316	316 Stainless Steel	1.7	N/A	22.22 mm	63.80 mm	N/A	3/8" Female NPT	10.0 mm	3/8" Female NPT
CV3-F-6N-BRAS	Brass	1.7	N/A	22.22 mm	63.80 mm	N/A	3/8" Female NPT	10.0 mm	3/8" Female NPT
CV3-H-8T-S316	316 Stainless Steel	1.7	22.22 mm	22.22 mm	80.20 mm	36.20 mm	1/2" Hy-Lok	10.0 mm	1/2" Hy-Lok
CV3-H-8T-BRAS	Brass	1.7	22.22 mm	22.22 mm	80.20 mm	36.20 mm	1/2" Hy-Lok	10.0 mm	1/2" Hy-Lok
CV3-H-12M-S316	316 Stainless Steel	1.7	22.00 mm	22.22 mm	80.20 mm	36.20 mm	12mm Hy-Lok	10.0 mm	12mm Hy-Lok
CV3-H-12M-BRAS	Brass	1.7	22.00 mm	22.22 mm	80.20 mm	36.20 mm	12mm Hy-Lok	10.0 mm	12mm Hy-Lok
CV3-M-8N-S316	316 Stainless Steel	1.7	N/A	22.22 mm	74.40 mm	36.20 mm	1/2" Male NPT	10.0 mm	1/2" Male NPT
CV3-M-8N-BRAS	Brass	1.7	N/A	22.22 mm	74.40 mm	36.20 mm	1/2" Male NPT	10.0 mm	1/2" Male NPT
CV4-F-8N-S316	316 Stainless Steel	2.6	N/A	28.58 mm	84.70 mm	N/A	1/2" Female NPT	13.5 mm	1/2" Female NPT
CV4-F-8N-BRAS	Brass	2.6	N/A	28.58 mm	84.70 mm	N/A	1/2" Female NPT	13.5 mm	1/2" Female NPT
CV4-H-10T-S316	316 Stainless Steel	2.6	25.40 mm	28.58 mm	91.80 mm	48.10 mm	5/8" Hy-Lok	13.5 mm	5/8" Hy-Lok
CV4-H-10T-BRAS	Brass	2.6	25.40 mm	28.58 mm	91.80 mm	48.10 mm	5/8" Hy-Lok	13.5 mm	5/8" Hy-Lok
CV5-H-12T-S316	316 Stainless Steel	5.2	28.56 mm	31.75 mm	110.70 mm	67.00 mm	3/4" Hy-Lok	16.0 mm	3/4" Hy-Lok
CV5-H-12T-BRAS	Brass	5.2	28.56 mm	31.75 mm	110.70 mm	67.00 mm	3/4" Hy-Lok	16.0 mm	3/4" Hy-Lok
CV5-M-12N-S316	316 Stainless Steel	5.2	N/A	31.75 mm	105.30 mm	67.00 mm	3/4" Male NPT	16.0 mm	3/4" Male NPT
CV5-M-12N-BRAS	Brass	5.2	N/A	31.75 mm	105.30 mm	67.00 mm	3/4" Male NPT	16.0 mm	3/4" Male NPT

Référence	Matériel	Cv	H	H1	L	I	Inlet End Connection	Orifice	Outlet End Connection
CV5-F-12N-S316	316 Stainless Steel	5.2	N/A	31.75 mm	103.00 mm	N/A	3/4" Female NPT	16.0 mm	3/4" Female NPT
CV5-F-12N-BRAS	Brass	5.2	N/A	31.75 mm	103.00 mm	N/A	3/4" Female NPT	16.0 mm	3/4" Female NPT
CV6-H-16T-S316	316 Stainless Steel	8.0	38.1 mm	34.93 mm	121.20 mm	68.40 mm	1" Hy-lok	18.0 mm	1" Hy-lok
CV6-H-16T-BRAS	Brass	8.0	38.1 mm	34.93 mm	121.20 mm	68.40 mm	1" Hy-lok	18.0 mm	1" Hy-lok
CV6-M-16N-S316	316 Stainless Steel	8.0	N/A	34.93 mm	116.20 mm	68.40 mm	1" Male NPT	18.0 mm	1" Male NPT
CV6-M-16N-BRAS	Brass	8.0	N/A	34.93 mm	116.20 mm	68.40 mm	1" Male NPT	18.0 mm	1" Male NPT
CV6-F-16N-S316	316 Stainless Steel	8.0	N/A	41.28 mm	111.4 mm	68.40 mm	1" Female NPT	18.0 mm	1" Female NPT
CV6-F-16N-BRAS	Brass	8.0	N/A	41.28 mm	111.4 mm	68.40 mm	1" Female NPT	18.0 mm	1" Female NPT